



Reg No. : 2003/096209/23 | VAT No. : 4090216435

Steinhoff Industrial Park, George

## RustArrestor™

**COLOR:** Clear

- BASIC USES:**
- Labor saving preparation for rust
  - Neutralizes rust and eliminates need for sandblasting
  - Loosens grime for easier cleaning
  - Improves coating effectiveness

**PRODUCT DESCRIPTION:** A package of two powerful cleaners simultaneously neutralize and dissolve surface rust as it stabilizes oxidation for coating with Topps Seal® water-free coatings. Applies by pump-up sprayer or rag mop at approximately 0.15 liters per square meter, followed by power wash after just 10 minutes. May be repeated if needed for heavy rust. In cases of heavier rust, allow to sit up to 30 minutes prior to power washing.

- FEATURES:**
- Easy to use
  - Clear
  - Leaves no film
  - Spreading Rate: 1 m<sup>2</sup> / 0.15 liter

**WET MATERIAL**  
*Typical Product Characteristics*

Viscosity	Water
Weight per gallon	4.5 – 5.0 kg
Flashpoint of solvent	>93°C
VOC	<150 g/l
pH	0 - 2
Dry to touch @ 25°C (50% rel. humidity)	<2 hours
Service Temperature	-40° - 60°C

The spreading rate (m<sup>2</sup>/L) is approximate only as it may be influenced by profile, textured or porous surfaces, and application method and tools.